

Standard Support Grips

Tuff-Seal Support Grips are designed to hold the weight of cable that is vertical or sloping. They are woven with non-magnetic, tinned bronze wire that absorbs strain and flexing while resisting cable pull-out, flexing and vibration. These Support Grips are available in a wide selection of eye styles and cable ranges, can be used either indoors or outdoors, and will support cable, metal rods and tubing with loads up to 600 lbs.



Closed Mesh— Double Eye—Single Weave

Cable Range	Catalog Numbers	Description	Approx.* Breaking Strength	Length Eye Mesh
.50- .62	2201-001	R050-DE	530	4 10
.63- .74	2201-002	R062-DE	790	4 10
.75- .99	2201-003	R075-DE	1020	4 13
1.00-1.24	2201-004	R100-DE	1610	5 14
1.25-1.49	2201-005	R125-DE	1610	5 15
1.50-1.74	2201-006	R150-DE	1610	5 17
1.75-1.99	2201-007	R175-DE	2150	6 19
2.00-2.49	2201-008	R200-DE	3260	6 21
2.50-2.99	2201-009	R250-DE	3260	6 23
3.00-3.49	2201-010	R300-DE	4900	8 25
3.50-3.99	2201-011	R350-DE	4900	8 27

Closed Mesh— Single Eye—Single Weave

Cable Range	Catalog Numbers	Description	Approx.* Breaking Strength	Length Eye Mesh
.50- .62	2201-013	R050-SE	530	7 10
.63- .74	2201-014	R062-SE	790	8 10
.75- .99	2201-015	R075-SE	1020	8 13
1.00-1.24	2201-016	R100-SE	1610	9 14
1.25-1.49	2201-017	R125-SE	1610	10 15
1.50-1.74	2201-018	R150-SE	1610	12 17
1.75-1.99	2201-019	R175-SE	2150	14 19
2.00-2.49	2201-020	R200-SE	3260	16 21
2.50-2.99	2201-021	R250-SE	3260	18 23
3.00-3.49	2201-022	R300-SE	4900	21 25
3.50-3.99	2201-023	R350-SE	4900	24 27

All mesh is available as double weave or stainless steel. Consult factory for availability.

